






UPHOLSTERY FABRIC SPECIFICATION

DESIGN	DIVINE	REPORT No.	A.C.T.007
CONTENT	60% Australian worsted wool 40% olefin		
WIDTH	54" (137cm)	DATE	11/15/01
ROLL SIZE	66yds (60m)	WEIGHT	12 oz sq yd (380gsm)
PATTERN REPEAT	H 1 1/8" (3.5cm) / V 3/8" (1.0cm)	RECOMMENDED CARE CODE	- S

Item	Test Method	Test Results
 Heavy Duty Upholstery	ASTM 3597 Wyzenbeek modified (#10 cotton duck) Report # 7-506872-MN	>100,000
	ASTM 4966 Martindale (21oz weight) Report # AN 315A/347	>40,000
	California Bulletin 117 Section E Report # Applied Textiles 93586	Compliance
	ASTM E 84 (unadhered method) ANSI 2.5, NFPA 255, UBC 42-1, UL 723 Report # Applied Textiles 93586	Flame Spread Index 20 Smoke Developed Index 200 Class 1 or A
	AATCC 8 Report # AN 944 B	Dry Crocking 4-5 Wet Crocking 4-5
	AATCC 16E Report # AWTA 7-504960-MN	5-6
	ASTM D5034 Breaking Strength Grab Method Report # AN 944 B	Warp – 173 lbs Weft – 186 lbs
	ASTM D 3511 Brush Pill Report # Applied Textiles 93586	4
	ASTM D3597-D434 Seam Slippage Report # AN 944 B	82 lbs
ENVIRONMENTAL INFORMATION SYSTEM	<u>Raw Materials</u> - 60% rapidly renewable content - 40% low-embodied-energy material : Olefin has a lower embodied energy compared to polyester and nylon <u>Production</u> - Environmental Improved Production Process : reduced energy & water consumption, reuse of water (30%), reuse/recycling of waste <u>Human Health</u> - Wool absorbs prevalent indoor air contaminants therefore benefiting indoor air quality <u>Disposal</u> - Reusable, recyclable and 60% biodegradable (wool content)	



APPROVED BY:
Louise Cramp, BSC Textile Technology, Product Manager.

REVISION: R107/01/021101