

# FLUTING

A unique high performance wallcovering featuring elegant vertical grooves.




INSTYLE


# FLUTING



Argos FLU004




Athens FLU001



Volos FLU011




Corinth FLU002



Kavala FLU009



Pylos FLU010



Sparta FLU007



Megara FLU008



Chalcis FLU005



Delphi FLU006




Thebes FLU003



Larissa FLU012

Patterns shown are not to scale  
Product may vary in colour due to the nature of the media  
Please refer to website for current colour range



FACE COMPOSITION	vinyl (PVC)
BACKING TYPE	osnaburg
WIDTH	130cm
WEIGHT	479gsm / 623g lineal m
PATTERN REPEAT	non-match
ROLL SIZE	29.3m approx. Note: minimum order quantity is 3.6m and 0.9m multiples
PERFORMANCE	Type II Wallcovering
FIRE RATING AS/NZS 3837	BCA Group 2 Av. Specific Extinction Area 653.4m2/kg
Additional Fire Tests	ASTM E-84 Tunnel Test: Class A EN 13501-1: Euroclass B

## PRODUCT INSTALLATION

- Please refer to installation instructions for FLUTING supplied with each shipment. A copy is also available on our website. Installation instructions should be referred to before cutting or installing this wallcovering.
- All material must be installed in numerical sequence as cut from the roll.

## CARE + MAINTENANCE

- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution. Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss. Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion. Rinse thoroughly with clean water from the top down using a sponge.
- Deeply embossed wallcoverings need extra attention in case suds or loosened dirt lodge in depressed surfaces.
- Dry wallcovering with a soft lint free cloth or towel.
- Please refer to the FLUTING care and maintenance instructions for further details.

## WARRANTY

- For a period of 3 years from date of invoice this wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only to professionally applied installations according to the recommended hanging instructions, and proper care and maintenance using appropriate cleaning agents as outlined in the care and maintenance instructions.